Diesel Extremest Fluid
Transfer Pump Systems

**Diesel Exhaust Fluid (DEF)** is for diesel engine vehicles which use Selective Catalytic Reduction (SCR) to control NOx emissions. Finish Thompson DEF Pump Systems easily, economically, and safely provide DEF transfer from a variety of containers into the vehicle's on-board storage tank. FTI DEF Pumps are designed for years of reliable service while maintaining the strict purity requirements for DEF (ISO 22241-3).

## **EFP Series**

## - Economical 5 GPM Solution\*

- Economical choice
- Available with a two-speed electric or air motor
- Ideal alternative to slow, troublesome hand pumps

### **PFM Series**

### - High Performance 10 GPM Solution\*

- Rugged, industrial quality
- Available with a variable speed 115V electric or air motor
- Produces higher flows and higher pressures
- · Best choice for totes

\*Rates obtained with automatic nozzle.



### Pump Kits Include:

- · Pump tube matched to container size
- Choice of motor
- Sealed solution bung adapter with buttress thread
- 8-feet of Goodyear® DEF dispensing hose with stainless steel clamp
- Stainless steel automatic shutoff nozzle

Note: Individual kit components and options are also available separately. See page 2

| DEF Pump Kits         |             |                   |         |         |  |  |
|-----------------------|-------------|-------------------|---------|---------|--|--|
| Container Size        | Pump Length | Motor Type        | EFP Kit | PFM Kit |  |  |
| 5-gallon bucket       | 16"         | 115-volt electric | DEFP007 | -       |  |  |
|                       |             | Air               | DEFP008 | -       |  |  |
| 30-gallon carboy      | 27"         | 115-volt electric | DEFP008 | -       |  |  |
|                       |             | Air               | DEFP012 | -       |  |  |
| 55-gallon drum        | 40"         | 115-volt electric | DEFP009 | DPFM011 |  |  |
|                       |             | Air               | DEFP013 | DPFM012 |  |  |
| 275-gallon tote (IBC) | 48"         | 115-volt electric | DEFP010 | DPFM013 |  |  |
|                       |             | Air               | DEFP014 | DPFM014 |  |  |
| 330-gallon tote (IBC) | 54"         | 115-volt electric | DEFP032 | -       |  |  |
|                       |             | Air               | DEFP033 | -       |  |  |

For more information on DEF handling, visit www.def-handling.com.





# **Options / Accessories**

### Sealed Solution Bung Adapter

Prevents dust and dirt from entering the container. Vents are easily removed for cleaning if necessary. Available in American buttress or NPT thread styles.

Note: Sealed Solution Bung Adapter included in pump kits.

| Fits Model | Container Thread Type | Part Number |
|------------|-----------------------|-------------|
| EFP        | Buttress              | 107383      |
| EFP        | NPT                   | 107384      |
| PFM        | Buttress              | 107418      |
| PFM        | NPT                   | 107419      |

### Stainless Steel Nozzle

· Stainless Steel Automatic Nozzle with 19 mm spout. Automatically stops fluid flow when tank is full. P/N 107231

#### **Hose Hanger**

Stores hose on side of drum. Part number - 107443

#### Hose

EPDM hose is peroxide cured and flushed with deionized water for purity.

Part number - 8' x 3/4" ID of hose. P/N 107446 Part number - per foot, clamp not included. P/N J101756

### **Individual Pump Components**

Build your own kit – complete pump requires pump tube and motor. Complete the package with any of the options shown above.

| Model              | Description   | Part Number |
|--------------------|---|-------------|
| EF Series          |   |             |
| EPF-16 pump tube   | 16" polypropylene tube w/ 316SS shaft – 5-gallons per minute  | DEFP001     |
| EFP-27 pump tube   | 27" polypropylene tube w/ 316SS shaft – 5-gallons per minute  | DEFP002     |
| EFP-40 pump tube   | 40" polypropylene tube w/ 316SS shaft – 5-gallons per minute  | DEFP003     |
| EFP-48 pump tube   | 48" polypropylene tube w/ 316SS shaft – 5-gallons per minute  | DEFP004     |
| EFP-54 pump tube   | 54" polypropylene tube w/ 316SS shaft – 5-gallons per minute  | DEFP038     |
| S1 electric motor  | 1/5 hp, 115-volt, 1 phase, 60 Hz motor                        | 107324-1    |
| S4 air motor       | Air motor w/muffler & control valve, 40 psi, 20 cfm air       | 107325      |
| PFM Series         |   |             |
| PFM-40             | 40" polypropylene tube w/ 316SS shaft – 10-gallons per minute | DPFM015     |
| PFM-48             | 48" polypropylene tube w/ 316SS shaft – 10-gallons per minute | DPFM016     |
| M3V electric motor | 1/2 hp, 115-volt, 1 phase, 60 Hz motor                        | 106655      |
| M6 air motor       | Air motor w/muffler & control valve, 80 psi, 25 cfm           | A100007     |

Note: Above PFM pumps have a 3/4" barb fitting for use with EPDM hose.

FINISH THOMPSON INC. 921 Greengarden Road • Erie, PA 16501-1591 U.S.A.

Ph 814-455-4478 . Fax 814-455-8518

#### Other DEF dispensing options available. Contact FTI for more information.



vent filters

Dual 80-micron

O-ring seals pump tube







