


**Mounting**

MSLL  
MSLL-BRACKET



\*ships w/ fixture



**Product Features**

- T5 based seamless dimming
- High efficiency built-in programmed start ballast
- End of Lamp life (EOL) protection
- Low profile rigid extruded aluminum body
- Compatible with many dimming signals using signal translator
- Quick connection system
- Daisy chain up to 10 fixtures together

**Specification**

- Frequency range: 60Hz
- Voltage: 110 -130V
- Power factor: > 97%
- Color Rendering Index (CRI) = Ra > 80
- Lamp life: 20,000hr
- Tube diameter: 16mm(T5)
- Class of protection: I
- Degree of protection: IP20
- Operating Temperature: 0-45 °C  
32-113 °F

**Warranty**

3 year warranty

**Certifications**



**Beam Angle**

270° = DSLL

**Notice**

Max connection : 10 fixtures  
14W HE (42 pcs) , 21W HE (28 pcs),  
28W HE (21 pcs)

**Dimming**

- Compatible with 0 to 10 LV Controller using signal interface
- Dimming down to 5% of max, output
- Compatible with Lutron Grafix Eye, homeworks, & Diva when communicating via 0 - 10

**Finish**

White powder coated finish (Standard)

**Weight**

DSLL 14 = 1.0 lbs.  
DSLL 21 = 1.2 lbs.  
DSLL 28 = 1.6 lbs.

**Shipment**

DimSlimLine Kits (fixture, lamps, options) do NOT ship assembled

**POWER SUPPLY & ACCESSORIES (PS)**

Maximum run length is 10 fixtures. Extended lengths require dimming booster. See Dimming Accessories.

**MODEL NO.**

DSLL\_14W = HE 14W Length 22 7/8" (582 mm)\*  
DSLL\_21W = HE 21W Length 34 11/16" (882 mm)\*  
DSLL\_28W = HE 28W Length 46 4/8" (1182 mm)\*

**COLOR / K**

22K = 2200K  
24K = 2400K  
27K = 2700K  
30K = 3000K  
35K = 3500K  
40K = 4000K  
65K = 6500K  
80K = 8000K

**VOLTAGE**

120V = 120 volts

**OPTIONS**

C = Cover (Polycarbonate diffuser)  
SLL14CV = Cover for 14/24W  
SLL21CV = Cover for 21W  
SLL28CV = Cover for 28W

**Accessories**

**CONNECTORS**

\_\_SLLCPL/XL = Direct connecting cap  
\_\_SLL-OUTLET CAP = Protecting cap for termination

Connecting Cable from fixture to fixture...

\_\_SLLPTC/XL = Connecting cable 6" (150mm)  
\_\_SLLPTC1/XL = Connecting cable 1' (300mm)  
\_\_SLLPTC2/XL = Connecting cable 2' (600mm)  
\_\_SLLPTC4/XL = Connecting cable 4' (1200mm)  
\_\_SLLPTC6/XL = Connecting cable 6' (1800mm)

Connecting Cable from Metal Hard Wire Box (MHWB) / Booster to first fixture...

\_\_DSLSLLPTC/XL = Connecting cable 6" (150mm)  
\_\_DSLSLLPTC1/XL = Connecting cable 1' (300mm)  
\_\_DSLSLLPTC2/XL = Connecting cable 2' (600mm)  
\_\_DSLSLLPTC4/XL = Connecting cable 4' (1200mm)  
\_\_DSLSLLPTC6/XL = Connecting cable 6' (1800mm)

Connecting Cable from fixture to Booster...

\_\_SLLSLLPTC/XL = Connecting cable 6" (150mm)  
\_\_SLLSLLPTC1/XL = Connecting cable 1' (300mm)  
\_\_SLLSLLPTC2/XL = Connecting cable 2' (600mm)  
\_\_SLLSLLPTC4/XL = Connecting cable 4' (1200mm)  
\_\_SLLSLLPTC6/XL = Connecting cable 6' (1800mm)

**POWER SUPPLY**

\_\_MHWB/ESL = Metal hard wire box

Other connector lengths available upon request

**PRODUCT SPECIFICATION EXAMPLE:**

DSLL_14W	22K	120V	C	STD	
MODEL	COLOR/K	VOLTAGE	OPTIONS	FINISH	REQUIRED POWER SUPPLY & ACCESSORIES*